

INTERNATIONAL JOURNALS FOR THE SEWING INDUSTRY

# JSN International

Head Office: 16-11, Oizumigakuen-machi 5-chome, Nerima-ku,  
Tokyo 178-0061, Japan Tel: (03) 3867-5815 Fax: (03) 3867-5603  
E-mail: jsn-intl@dd.iij4u.or.jp Website: www.jsn-intl.com

AUGUST 2016



# VI.BE.MAC'S FEED OF THE ARM 2261 HP

Vi.Be.Mac. is one of the leading Company in Automatic Sewing Machines Area.

Its business in India has been successful for almost three decades, and it'll continue to be one of the key markets thanks to the long lasting business cooperation with E.H. Turel Company, the first overseas agent for Vi.Be.Mac.

Between Vi.Be.Mac.'s best sellers, there is the high performances 3 needle chain stitch automatic feed of the arm unit, strong, fast, precise, consistent in the stitch length even on the thickest parts! The 2261HP is feed off the arm unit, 3 needle chain stitch, for double lap seaming on jeans,



2261HP

casual trousers, work clothes and denim clothes in general. This machine is particularly suitable to sew back yoke, back rise, inseam and out seams, plus top stitch operations. Does not have rivals also when used for shirts. Vibemac's feed of the arm is provided with a special belt puller, that grants very fast feeding and perfect matching between the sewn parts. In terms of productivity, 2261HP can work at 4999 rpm, this high speed can be achieved only thanks to several outstanding features, like oil feeding lubrication, design and construction quality, puller device and a special sensor for the dynamic pressure presser foot control (DCP system). The above mentioned DCP system avoids all the skip stitching troubles also on the crotch double thickness, the most critical point for every feed of the arm machine existing in the market.

The machine's features can be listed as follow:

- Always High And Constant Quality: thanks to the special & patented DCP system, the stitching length will be constant and the operator's job much easier (no need to pull/push to match 2 parts)
- Higher Production: the unit's speed (4999 rpm) associated with the smart puller system allows a production incomparable in the market, up to 5 inseams in 1 minute!
- Great flexibility: different needle gauges grant maximum flexibility, the machine is provided to sew heavy materials but it is also possible to modify it by purchasing the light fabric kit

## 2261HP FEED OF THE ARM UNIT

FOLLOW US!!

### SPECIFICATIONS

- ✓ Max Sewing Speed: 4999 rpm
- ✓ Stitching Length: from 0,9 to 4,5 mm
- ✓ Standard Needle Gauge: 1/4" (6,4 mm)
- ✓ Optional Needle Gauge: 9/32" (7,2 mm)  
3/8" (9,6 mm) - 1/4" + 1/8" (MIX 9,6 mm)  
3/16" (4,8 mm) 2 needles - 5/16" (7,9 mm)
- ✓ Sewing Head: Vi.Be.Mac. 3 needle chain stitch

**5 INSEAM PER MINUTE**  
PRODUCTION RATE INCOMPARABLE IN THE MARKET!

---

**CONSTANT STITCHING LENGTH**  
THANKS TO THE PULLER AND THE PATENTED DCP SYSTEM

DISTRIBUTES

For info, write an email @ [sales@vbm-grp.com](mailto:sales@vbm-grp.com) or contact vbm local branches @ the addresses:  
[sales@vbm-in.com](mailto:sales@vbm-in.com) (INDIA) | [sales@vbm-bd.com](mailto:sales@vbm-bd.com) (BANGLADESH) |  
[sales@vbm-ae.com](mailto:sales@vbm-ae.com) (U.A.E.) | [sales@vbm-eg.com](mailto:sales@vbm-eg.com) (EGYPT) |  
[sales@vbm-mx.com](mailto:sales@vbm-mx.com) (MEXICO)

**VI.BE.MAC. Spa:** 37057 S. Giovanni Lupatoto (VR) Italy  
 ph. +39 045 8778151 - fax +39 045 8779024 - [www.vibemac.com](http://www.vibemac.com)

- Pneumatic trimming device with sensor, to guarantee extreme precision and waste reduced to zero.

For more informations, please visit our website: [www.vibemac.com](http://www.vibemac.com) or write us an e-mail at [vibemac@vibemac.com](mailto:vibemac@vibemac.com). If you want to see our units working in a real production line, please visit our youtube page: [www.youtube.com/VIBEMACSpa](http://www.youtube.com/VIBEMACSpa) or scan the below QR code.



Circle # 55 on Reader Service Card

---